



Simulation of stretch in non-uniform filaments.

Szabo, Peter; Clasen, Christian; McKinley, Gareth H.

Publication date:
2012

[Link back to DTU Orbit](#)

Citation (APA):

Szabo, P., Clasen, C., & McKinley, G. H. (2012). *Simulation of stretch in non-uniform filaments.* Abstract from 17th International Workshop on Numerical Methods for Non-Newtonian Flows, Blois, France.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Simulation of stretch in non-uniform filaments.

Peter Szabo¹, Christian Clasen² and Gareth H. McKinley³

¹Dept. of Chemical and Biochemical Engineering, DTU, DK-2800 Lyngby, Denmark,

²Dept. of Chemical Engineering, Katholieke Universiteit Leuven, Belgium,

³Dept. of Mechanical Engineering, MIT, Cambridge, Massachusetts, USA.

December 14, 2011

Abstract

We consider the rapid stretching of a liquid filament under the action of a constant imposed tensile force. This problem was first considered experimentally by Matta and Tytus (1990). A liquid bridge formed from a dilute polymer solution is established between two cylindrical disks. The upper disk is held fixed while the lower cylinder falls due to gravity.

With this constant force pull (CFP) technique it is possible to impose very large material strains and strain rates so that the maximum extensibility of the polymer molecules may be quantified. This characteristic of the experiment is analyzed numerically using FENE type models and two alternative kinematic descriptions. The axisymmetric filament is described by a Lagrangian approach based on an average stretch of axial elements (see Renardy (1990)). A no-slip boundary condition is imposed indirectly at the end-plates according to a method described by Tuck *et al.* (2000). An alternative uniform filament description is developed and compared to the more accurate Lagrangian model. The agreement between the two numerical techniques is evaluated in the time domain as well as in terms of Hencky strain.

References

1. J.E. Matta and R.P. Tytus, J. Non-Newton. Fluid Mech. 35 (1990) 215-229.
2. M. Renardy, J. Non-Newton. Fluid Mech. 51 (1994) 97-107.
3. Y.M. Stokes, E.O. Tuck and L.W. Schwartz, Quart. J. Mech. Appl. Math. 53 (2000) 565-582.

Abstract for IWNMNNF2012, Blois, France.